

TECHNICAL SPECIFICATION


Item	SPEC									Test Condition
Operating Temp	-55℃~+125℃									
C _R Range	0.10μF~680μF									25℃, 120Hz
C _R Tolerance	±10% or ±20%									25℃, 120Hz
Rated Voltage (V _R)	2.5V	4V	6.3V	10V	16V	20V	25V	35V	50V	85℃
Category Voltage (V _C)	1.6V	2.5V	4V	6.3V	10V	13V	16V	20V	32V	125℃
Surge Voltage (V _S)	3.3V	5.2V	8V	13V	20V	26V	32V	46V	65V	85℃
Surge Voltage (V _S)	2.2V	3.4V	5V	8V	13V	16V	20V	28V	40V	125℃

STANDARD C-V VALUE BY CASE CODE

Rated Voltage (V _R)	2.5	4	6.3	10	16	20	25	35	50
Voltage Code	e	G	J	A	C	D	E	V	T
C _R (μF)	C Code	Case Code							
0.1	104					P		A/P	A
0.15	154					P		A	B/A
0.22	224					P	A	A	B/A
0.33	334					P	A	A	B/A
0.47	474				P	A/P	A/P	B/A	C/B/A
0.68	684			P	A/P	A/P	B/A	B/A	C/B/A
1.0	105		A/P	A/P	A/P	B/A/P	B/A/P	B/A	C/B
1.5	155		A/P	A/P	B/A/P	B/B/A	B/A	C/B	C/B
2.2	225	A	A/P	B/A/P	B/A/P	B/A	C/B/A	C/B/A	D/C/B
3.3	335	A/P	B/A/P	B/A/P	B/A	C/B/A	C/B/A	C/B	D/C/B
4.7	475	B/A/P	B/A/P	B//A/P	C/B/A/P	C/B/A	D/C/B/A	D/C/B	D
6.8	685	B/A/P	B/A/P	C/B/A/P	C/B/A	D/C/B	D/C/B	D/C	D
10	106	A/P	B/A/P	C/B/A/P	C/B/A/P	C/B/A	D/C/B	D/C/B	E/D/C
15	156	B/A	C/B/A	C/B/A/P	C/B/A	D/C/B	D/C	D/C/B	E/D
22	226	A/P	C/B/A	D/B/A/P	D/C/B/A	D/C/B/A	D/C/B	D/C	E/D
33	336	A/P	D/C/B/A/P	D/C/B/A	D/C/B/A	D/C/B	D/C	E/D	E
47	476	A	D/C/B/A/P	D/C/B/A	D/C/B/A	D/C/B	E/D/C	E/D	E
68	686	B/A	D/C/B	D/C/B	D/C/B	D	E/D	E	
100	107	B/A	D/C/B/A	D/C/B/A	D/C/B	D/C	E/D	D	
150	157	B	D/C/B	D/C/B	E/D/C	E/D	E		
220	227	B	D/C/B	E/D/C/B	E/D	E/D			
330	337		E/D/C/B	E/D	E/D	E			
470	477		E	E/D	E				
680	687		E						

※: The first case code is standard product and the others are expansion products.

CONSTRUCTION



MARKINGS



Rated Voltage Code

Rated Voltage(V_R)	2.5	4	6.3	10	16	20	25	35	50
Code	e	G	J	A	C	D	E	V	T

Capacitance Code

Capacitance (μF)	0.1	0.15	0.22	0.33	0.47	0.68	1.0	1.5	2.2	3.3	4.7	6.8
Code (P Case)	<u>A</u>	<u>E</u>	<u>J</u>	<u>N</u>	<u>S</u>	<u>W</u>	A	E	J	N	S	W
Code (A/B/C/D/E Case)	104	154	224	334	474	684	105	155	225	335	475	685
Capacitance (μF)	10	15	22	33	47	68	100	150	220	330	470	680
Code (P Case)	<u>A</u>	<u>E</u>	<u>J</u>	<u>N</u>	<u>S</u>	<u>W</u>						
Code (A/B/C/D/E Case)	106	156	226	336	476	686	107	157	227	337	477	687

SPECIFICATIONS

TC211 TYPE

Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.	Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.
2.5V, +85°C (1.6V @ +125°C)						2.5V, +85°C (1.6V @ +125°C)					
10.0	P	TC211P106◎002□	0.5	6.0	6.0	220.0	D	TC211D227◎004Y	8.8	8.0	0.8
10.0	A	TC211A106◎002□	0.5	6.0	5.0	330.0	B	TC211B337◎004□	13.2	18.0	1.2
15.0	A	TC211A156◎002□	0.5	6.0	6.0	330.0	C	TC211C337◎004Y	13.2	8.0	1.2
15.0	B	TC211B156◎002□	0.5	6.0	4.0	330.0	D	TC211D337◎004Y	13.2	8.0	0.7
22.0	P	TC211P226◎002□	0.55	20.0	6.0	330.0	E	TC211E337◎004Y	13.2	8.0	0.7
22.0	A	TC211A226◎002□	0.55	6.0	4.0	470.0	E	TC211E477◎004Y	18.8	8.0	0.8
33.0	P	TC211P336◎002□	0.82	15.0	6.0	680.0	E	TC211E687◎004Y	27.2	8.0	0.5
33.0	A	TC211A336◎002□	0.82	6.0	4.0	6.3V, +85°C (4.0V @ +125°C)					
47.0	A	TC211A476◎002□	1.17	10.0	4.0	1.0	P	TC211P105◎006□	0.5	6.0	25.0
68.0	A	TC211A686◎002□	1.7	10.0	3.0	1.0	A	TC211A105◎006□	0.5	6.0	14.0
68.0	B	TC211B686◎002□	1.7	6.0	2.0	1.5	P	TC211P155◎006□	0.5	8.0	25.0
100.0	A	TC211A107◎002□	2.5	20.0	2.5	1.5	A	TC211A155◎006□	0.5	6.0	8.0
100.0	B	TC211B107◎002□	2.5	8.0	1.5	2.2	P	TC211P225◎006□	0.5	8.0	20.0
150.0	B	TC211B157◎002□	3.75	10.0	2.0	2.2	A	TC211A225◎006□	0.5	6.0	8.0
220.0	B	TC211B227◎002□	5.5	18.0	2.0	3.3	P	TC211P335◎006□	0.5	6.0	10.0
4V, +85°C (2.5V @ +125°C)						3.3	A	TC211A335◎006□	0.5	6.0	8.0
2.2	A	TC211A225◎004□	0.5	6.0	8.0	4.7	P	TC211P475◎006□	0.5	6.0	10.0
3.3	P	TC211P335◎004□	0.5	6.0	10.0	4.7	A	TC211A475◎006□	0.5	6.0	6.0
3.3	A	TC211A335◎004□	0.5	6.0	8.0	6.8	P	TC211P685◎006□	0.5	6.0	10.0
4.7	P	TC211P475◎004□	0.5	6.0	10.0	6.8	A	TC211A685◎006□	0.5	6.0	6.0
4.7	A	TC211A475◎004□	0.5	6.0	8.0	6.8	B	TC211B685◎006□	0.5	6.0	3.5
6.8	P	TC211P685◎004□	0.5	6.0	10.0	10.0	P	TC211P106◎006□	0.63	8.0	10.0
6.8	A	TC211A685◎004□	0.5	6.0	6.0	10.0	A	TC211A106◎006□	0.63	6.0	4.0
10.0	P	TC211P106◎004□	0.5	8.0	10.0	10.0	B	TC211B106◎006□	0.63	6.0	3.5
10.0	A	TC211A106◎004□	0.5	6.0	6.0	15.0	P	TC211P156◎006□	0.94	10.0	7.0
10.0	B	TC211B106◎004□	0.5	6.0	3.5	15.0	A	TC211A156◎006□	0.94	6.0	4.0
15.0	A	TC211A156◎004□	0.6	6.0	4.0	15.0	B	TC211B156◎006□	0.94	6.0	3.5
15.0	B	TC211B156◎004□	0.6	6.0	3.5	22.0	P	TC211P226◎006□	1.3	18.0	6.0
22.0	A	TC211A226◎004□	0.88	6.0	4.0	22.0	A	TC211A226◎006□	1.38	6.0	4.0
22.0	B	TC211B226◎004□	0.88	6.0	3.5	22.0	B	TC211B226◎006□	1.38	6.0	3.5
33.0	P	TC211P336◎004□	1.32	20.0	4.5	33.0	A	TC211A336◎006□	2.07	8.0	4.5
33.0	A	TC211A336◎004□	1.32	6.0	4.0	33.0	B	TC211B336◎006□	2.07	6.0	3.0
33.0	B	TC211B336◎004□	1.32	6.0	3.5	33.0	C	TC211C336◎006Y	2.07	6.0	1.8
33.0	C	TC211C336◎004Y	1.32	6.0	1.8	47.0	A	TC211A476◎006□	2.96	8.0	3.5
47.0	P	TC211P476◎004□	3.80	25.0	6.0	47.0	B	TC211B476◎006□	2.96	6.0	3.0
47.0	A	TC211A476◎004□	1.88	6.0	3.0	47.0	C	TC211C476◎006Y	2.96	6.0	1.6
47.0	B	TC211B476◎004□	1.88	6.0	3.0	68.0	B	TC211B686◎006□	4.28	10.0	1.2
47.0	C	TC211C476◎004Y	1.88	6.0	1.8	68.0	C	TC211C686◎006Y	4.28	6.0	1.0
68.0	B	TC211B686◎004□	2.72	6.0	3.5	68.0	D	TC211D686◎006Y	4.28	6.0	0.8
68.0	C	TC211C686◎004Y	2.72	6.0	1.6	100.0	A	TC211A107◎006□	6.3	20.0	4.0
68.0	D	TC211D686◎004Y	2.72	6.0	0.8	100.0	B	TC211B107◎006□	6.3	10.0	3.0
100.0	A	TC211A107◎004□	4.0	18.0	5.0	100.0	C	TC211C107◎006Y	6.3	8.0	1.2
100.0	B	TC211B107◎004□	4.0	8.0	2.0	100.0	D	TC211D107◎006Y	6.3	8.0	0.8
100.0	C	TC211C107◎004Y	4.0	8.0	1.3	150.0	B	TC211B157◎006□	9.45	15.0	1.0
100.0	D	TC211D107◎004Y	4.0	8.0	0.8	150.0	C	TC211C157◎006Y	9.45	8.0	1.2
150.0	B	TC211B157◎004□	6.0	15.0	2.0	150.0	D	TC211D157◎006Y	9.45	8.0	0.8
150.0	C	TC211C157◎004Y	6.0	8.0	1.2	220.0	B	TC211B227◎006□	13.86	18.0	1.0
150.0	D	TC211D157◎004Y	6.0	8.0	0.8	220.0	C	TC211C227◎006Y	13.86	8.0	1.2
220.0	B	TC211B227◎004□	8.8	15.0	0.5	220.0	D	TC211D227◎006Y	13.86	8.0	0.7
220.0	C	TC211C227◎004Y	8.8	8.0	1.0	220.0	E	TC211E227◎006Y	13.86	8.0	0.5
						330.0	D	TC211D337◎006Y	20.79	8.0	0.5

Sunlord

Specifications subject to change without notice. Please check our website for latest information. Revised 2014/10/15

Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110 Tel: 0086-755-29832660 Fax: 0086-755-82269029 E-Mail: sunlord@sunlordinc.com

SPECIFICATIONS

TC211 TYPE

Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.
330.0	E	TC211E337◎006Y	20.79	8.0	0.5
470.0	D	TC211D477◎006Y	29.61	12.0	0.4
470.0	E	TC211E477◎006Y	29.61	10.0	0.5
10V, +85°C (6.3V @ +125°C)					
0.68	P	TC211P684◎010□	0.5	4.0	28.0
1.0	P	TC211P105◎010□	0.5	10.0	25.0
1.0	A	TC211A105◎010□	0.5	4.0	13.0
1.5	P	TC211P155◎010□	0.5	10.0	10.0
1.5	A	TC211A155◎010□	0.5	6.0	8.0
2.2	P	TC211P225◎010□	0.5	6.0	10.0
2.2	A	TC211A225◎010□	0.5	6.0	8.0
3.3	P	TC211P335◎010□	0.5	6.0	15.0
3.3	A	TC211A335◎010□	0.5	6.0	6.0
4.7	P	TC211P475◎010□	0.5	6.0	10.0
4.7	A	TC211A475◎010□	0.5	6.0	6.0
4.7	B	TC211B475◎010□	0.5	6.0	3.5
6.8	P	TC211P685◎010□	0.68	8.0	5.0
6.8	A	TC211A685◎010□	0.68	6.0	6.0
6.8	B	TC211B685◎010□	0.68	6.0	3.5
10.0	P	TC211P106◎010□	1.0	15.0	10.0
10.0	A	TC211A106◎010□	1.0	6.0	4.0
10.0	B	TC211B106◎010□	1.0	6.0	3.5
10.0	C	TC211C106◎010Y	1.0	6.0	1.8
15.0	A	TC211A156◎010□	1.5	6.0	6.0
15.0	B	TC211B156◎010□	1.5	6.0	3.5
15.0	C	TC211C156◎010Y	1.5	6.0	1.8
22.0	A	TC211A226◎010□	2.2	8.0	4.0
22.0	B	TC211B226◎010□	2.2	6.0	3.0
22.0	C	TC211C226◎010Y	2.2	6.0	1.8
33.0	A	TC211A336◎010□	3.3	15.0	6.0
33.0	B	TC211B336◎010□	3.3	6.0	3.5
33.0	C	TC211C336◎010Y	3.3	6.0	1.6
33.0	D	TC211D336◎010Y	3.3	6.0	0.8
47.0	A	TC211A476◎010□	4.7	15.0	4.0
47.0	B	TC211B476◎010□	4.7	6.0	1.0
47.0	C	TC211C476◎010Y	4.7	6.0	1.2
47.0	D	TC211D476◎010Y	4.7	6.0	0.8
68.0	B	TC211B686◎010□	6.8	10.0	3.0
68.0	C	TC211C686◎010Y	6.8	6.0	1.2
68.0	D	TC211D686◎010Y	6.8	6.0	0.8
100.0	B	TC211B107◎010□	10.0	15.0	1.5
100.0	C	TC211C107◎010Y	10.0	8.0	1.2
100.0	D	TC211D107◎010Y	10.0	8.0	0.7
150.0	C	TC211C157◎010Y	15.0	10.0	0.9
150.0	D	TC211D157◎010Y	15.0	8.0	0.7
150.0	E	TC211E157◎010Y	15.0	8.0	0.5
220.0	D	TC211D227◎010Y	22.0	8.0	0.5
220.0	E	TC211E227◎010Y	22.0	8.0	0.5
330.0	D	TC211D337◎010Y	33.0	10.0	0.5
330.0	E	TC211E337◎010Y	33.0	10.0	0.5
470.0	E	TC211E477◎010Y	47.0	10.0	0.5

Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.
16V, +85°C (10V @ +125°C)					
0.47	P	TC211P474◎016□	0.5	6.0	25.0
0.68	P	TC211P684◎016□	0.5	6.0	25.0
1.0	P	TC211P105◎016□	0.5	6.0	25.0
1.0	A	TC211A105◎016□	0.5	4.0	10.0
1.5	P	TC211P155◎016□	0.5	6.0	20.0
1.5	A	TC211A155◎016□	0.5	6.0	8.0
2.2	P	TC211P225◎016□	0.5	6.0	25.0
2.2	A	TC211A225◎016□	0.5	6.0	6.0
2.2	B	TC211B225◎016□	0.5	6.0	4.0
3.3	A	TC211A335◎016□	0.52	6.0	6.0
3.3	B	TC211B335◎016□	0.52	6.0	3.5
4.7	P	TC211P475◎016□	0.8	18.0	15.0
4.7	A	TC211A475◎016□	0.75	6.0	6.0
4.7	B	TC211B475◎016□	0.75	6.0	3.5
4.7	C	TC211C475◎016Y	0.8	6.0	2.4
6.8	A	TC211A685◎016□	1.08	6.0	7.0
6.8	B	TC211B685◎016□	1.08	6.0	3.5
6.8	C	TC211C685◎016Y	1.08	6.0	2.0
10.0	A	TC211A106◎016□	1.6	8.0	7.0
10.0	B	TC211B106◎016□	1.6	6.0	2.8
10.0	C	TC211C106◎016Y	1.6	6.0	1.8
15.0	B	TC211B156◎016□	2.4	6.0	3.0
15.0	C	TC211C156◎016Y	2.4	6.0	1.8
22.0	A	TC211A226◎016□	3.52	15.0	4.0
22.0	B	TC211B226◎016□	3.52	8.0	2.2
22.0	C	TC211C226◎016Y	3.52	6.0	1.6
22.0	D	TC211D226◎016Y	3.52	6.0	0.8
33.0	B	TC211B336◎016□	5.28	8.0	2.0
33.0	C	TC211C336◎016Y	5.28	6.0	1.2
33.0	D	TC211D336◎016Y	5.28	6.0	0.8
47.0	B	TC211B476◎016□	7.52	18.0	1.0
47.0	C	TC211C476◎016Y	7.52	6.0	1.2
47.0	D	TC211D476◎016Y	7.52	6.0	0.8
68.0	D	TC211D686◎016Y	10.8	6.0	0.8
100.0	C	TC211C107◎016Y	16.0	10.0	1.0
100.0	D	TC211D107◎016Y	16.0	8.0	0.7
150.0	D	TC211D157◎016Y	24.0	12.0	0.7
150.0	E	TC211E157◎016Y	24.0	8.0	0.5
220.0	D	TC211D227◎016Y	35.2	15.0	0.9
220.0	E	TC211E227◎016Y	35.2	10.0	0.5
330.0	E	TC211E337◎016Y	52.8	10.0	0.5
20V, +85°C (13V @ +125°C)					
0.1	P	TC211P104◎020□	0.5	4.0	25.0
0.15	P	TC211P154◎020□	0.5	4.0	25.0
0.22	P	TC211P224◎020□	0.5	4.0	25.0
0.33	P	TC211P334◎020□	0.5	4.0	25.0
0.47	P	TC211P474◎020□	0.5	4.0	25.0
0.68	P	TC211P684◎020□	0.5	4.0	25.0
0.68	A	TC211A684◎020□	0.5	4.0	12.0
1.0	P	TC211P105◎020□	0.5	6.0	15.5

Sunlord

Specifications subject to change without notice. Please check our website for latest information. Revised 2014/04/15

Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110 Tel: 0086-755-29832660 Fax: 0086-755-82269029 E-Mail: sunlord@sunlordinc.com

SPECIFICATIONS

TC211 TYPE

Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.	Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.
1.0	A	TC211A105○020□	0.5	4.0	10.0	6.8	C	TC211C685○025Y	1.7	6.0	1.9
1.5	A	TC211A155○020□	0.5	6.0	8.0	6.8	D	TC211D685○025Y	1.7	6.0	1.2
1.5	B	TC211B155○020□	0.5	6.0	5.0	10.0	B	TC211B106○025□	2.5	6.0	3.0
2.2	A	TC211A225○020□	0.5	6.0	7.0	10.0	C	TC211C106○025Y	2.5	6.0	1.5
2.2	B	TC211B225○020□	0.5	6.0	3.5	10.0	D	TC211D106○025Y	2.5	6.0	1.0
3.3	A	TC211A335○020□	0.66	6.0	7.0	15.0	B	TC211B156○025□	3.75	8.0	4.0
3.3	B	TC211B335○020□	0.66	6.0	3.5	15.0	C	TC211C156○025Y	3.75	6.0	1.5
4.7	A	TC211A475○020□	0.94	6.0	4.0	15.0	D	TC211D156○025Y	3.75	6.0	1.0
4.7	B	TC211B475○020□	0.94	6.0	3.5	22.0	C	TC211C226○025Y	5.5	6.0	1.4
4.7	C	TC211C475○020Y	0.94	6.0	2.4	22.0	D	TC211D226○025Y	5.5	6.0	0.8
6.8	B	TC211B685○020□	1.36	6.0	3.5	33.0	D	TC211D336○025Y	8.25	6.0	0.8
6.8	C	TC211C685○020Y	1.36	6.0	2.0	33.0	E	TC211E336○025Y	8.25	6.0	0.7
6.8	D	TC211D685○020Y	1.36	6.0	1.9	47.0	D	TC211D476○025Y	11.7	6.0	0.8
10.0	B	TC211B106○020□	2.0	6.0	3.0	47.0	E	TC211E476○025Y	11.7	6.0	0.7
10.0	C	TC211C106○020Y	2.0	6.0	1.8	68.0	E	TC211E686○025Y	17.0	6.0	0.7
10.0	D	TC211D106○020Y	2.0	6.0	1.0	100.0	D	TC211D107○025Y	25.0	10.0	1.2
15.0	C	TC211C156○020Y	3.0	6.0	1.7	35V, +85°C (20V @ +125°C)					
15.0	D	TC211D156○020Y	3.0	6.0	1.0	0.1	P	TC211P104○035□	0.5	4.0	30.0
22.0	B	TC211B226○020□	4.4	8.0	4.0	0.1	A	TC211A104○035□	0.5	4.0	20.0
22.0	C	TC211C226○020Y	4.4	6.0	1.2	0.15	A	TC211A154○035□	0.5	4.0	19.0
22.0	D	TC211D226○020Y	4.4	6.0	0.8	0.22	A	TC211A224○035□	0.5	4.0	18.0
33.0	C	TC211C336○020Y	6.6	6.0	1.2	0.33	A	TC211A334○035□	0.5	4.0	15.0
33.0	D	TC211D336○020Y	6.6	6.0	0.8	0.47	A	TC211A474○035□	0.5	4.0	14.0
47.0	C	TC211C476○020Y	9.4	10.0	1.0	0.47	B	TC211B474○035□	0.5	4.0	8.0
47.0	D	TC211D476○020Y	9.4	6.0	0.8	0.68	A	TC211A684○035□	0.5	4.0	10.0
47.0	E	TC211E476○020Y	9.4	6.0	0.8	0.68	B	TC211B684○035□	0.5	4.0	6.5
68.0	D	TC211D686○020Y	13.6	6.0	0.8	1.0	A	TC211A105○035□	0.5	4.0	10.0
68.0	E	TC211E686○020Y	13.6	6.0	0.8	1.0	B	TC211B105○035□	0.5	4.0	5.0
100.0	D	TC211D107○020Y	20.0	8.0	0.6	1.5	B	TC211B155○035□	0.52	6.0	5.0
100.0	E	TC211E107○020Y	20.0	8.0	0.5	1.5	C	TC211C155○035Y	0.52	6.0	4.5
150.0	E	TC211E157○020Y	30.0	8.0	0.5	2.2	A	TC211A225○035□	0.77	6.0	6.0
25V, +85°C (16V @ +125°C)						2.2	B	TC211B225○035□	0.77	6.0	4.0
0.22	A	TC211A224○025□	0.5	4.0	15.0	2.2	C	TC211C225○035Y	0.77	6.0	3.5
0.33	A	TC211A334○025□	0.5	4.0	15.0	3.3	B	TC211B335○035□	1.15	6.0	3.5
0.47	A	TC211A474○025□	0.5	4.0	14.0	3.3	C	TC211C335○035Y	1.15	6.0	2.5
0.47	P	TC211P474○025□	0.5	4.0	13.0	4.7	B	TC211B475○035□	1.64	6.0	2.0
0.68	A	TC211A684○025□	0.5	4.0	10.0	4.7	C	TC211C475○035Y	1.64	6.0	2.5
1.0	P	TC211P105○025□	0.5	6.0	12.0	4.7	D	TC211D475○035Y	1.64	6.0	1.5
1.0	A	TC211A105○025□	0.5	4.0	8.0	6.8	C	TC211C685○035Y	2.38	6.0	2.0
1.0	B	TC211B105○025□	0.5	4.0	5.0	6.8	D	TC211D685○035Y	2.38	6.0	1.5
1.5	A	TC211A155○025□	0.5	6.0	10.0	10.0	C	TC211C106○035Y	3.5	6.0	2.0
1.5	B	TC211B155○025□	0.5	6.0	5.0	10.0	D	TC211D106○035Y	3.5	6.0	1.0
2.2	A	TC211A225○025□	0.6	6.0	6.0	10.0	E	TC211E106○035Y	3.5	6.0	1.0
2.2	B	TC211B225○025□	0.55	6.0	4.5	15.0	D	TC211D156○035Y	5.25	6.0	1.0
2.2	C	TC211C225○025Y	0.55	6.0	3.5	15.0	E	TC211E156○035Y	5.25	6.0	0.9
3.3	A	TC211A335○025□	0.82	6.0	7.0	22.0	D	TC211D226○035Y	7.7	6.0	0.8
3.3	B	TC211B335○025□	0.82	6.0	3.5	22.0	E	TC211E226○035Y	7.7	6.0	0.7
3.3	C	TC211C335○025Y	0.82	6.0	2.5	33.0	E	TC211E336○035Y	11.0	6.0	0.6
4.7	A	TC211A475○025□	1.17	8.0	6.0	47.0	E	TC211E476○035Y	16.5	8.0	0.6
4.7	B	TC211B475○025□	1.17	6.0	2.0	50V, +85°C (32V @ +125°C)					
4.7	C	TC211C475○025Y	1.17	6.0	2.4	0.1	A	TC211A104○050□	0.5	4.0	22.0
6.8	B	TC211B685○025□	1.7	6.0	3.0	0.15	A	TC211A154○050□	0.5	4.0	19.0

SPECIFICATIONS

TC211 TYPE

Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.
0.15	B	TC211B154◎050□	0.5	4.0	16.0
0.22	A	TC211A224◎050□	0.5	4.0	18.0
0.22	B	TC211B224◎050□	0.5	4.0	14.0
0.33	A	TC211A334◎050□	0.5	4.0	15.0
0.33	B	TC211B334◎050□	0.5	4.0	10.0
0.47	A	TC211A474◎050□	0.5	4.0	3.0
0.47	B	TC211B474◎050□	0.5	4.0	9.0
0.47	C	TC211C474◎050Y	0.5	4.0	8.0
0.68	A	TC211A684◎050□	0.5	4.0	4.0
0.68	B	TC211B684◎050□	0.5	4.0	8.0
0.68	C	TC211C684◎050Y	0.5	4.0	7.0
1.0	B	TC211B105◎050□	0.5	6.0	6.0
1.0	C	TC211C105◎050Y	0.5	4.0	5.5

Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.
1.5	B	TC211B155◎050□	0.75	6.0	4.5
1.5	C	TC211C155◎050Y	0.75	6.0	3.5
2.2	B	TC211B225◎050□	1.1	6.0	2.0
2.2	C	TC211C225◎050Y	1.1	6.0	3.5
2.2	D	TC211D225◎050Y	1.1	6.0	2.5
3.3	B	TC211B335◎050□	1.65	6.0	1.7
3.3	C	TC211C335◎050Y	1.65	6.0	3.0
3.3	D	TC211D335◎050Y	1.65	6.0	2.0
4.7	D	TC211D475◎050Y	2.35	6.0	1.5
6.8	D	TC211D685◎050Y	3.4	6.0	1.2
10.0	D	TC211D106◎050Y	5.0	6.0	1.0
10.0	E	TC211E106◎050Y	5.0	6.0	0.7
15.0	E	TC211E156◎050Y	7.5	6.0	0.7

TC212 TYPE

Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.
2.5V, +85°C (1.6V @ +125°C)					
10.0	P	TC212P106◎002□	0.5	6.0	5.0
10.0	A	TC212A106◎002□	0.5	6.0	4.0
15.0	A	TC212A156◎002□	0.5	6.0	4.0
15.0	B	TC212B156◎002□	0.5	6.0	3.0
22.0	P	TC212P226◎002□	0.55	20.0	4.0
22.0	A	TC212A226◎002□	0.55	6.0	3.0
33.0	P	TC212P336◎002□	0.82	15.0	4.0
33.0	A	TC212A336◎002□	0.82	6.0	3.0
47.0	A	TC212A476◎002□	1.17	10.0	3.0
68.0	A	TC212A686◎002□	1.7	10.0	2.5
68.0	B	TC212B686◎002□	1.7	6.0	1.8
100.0	A	TC212A107◎002□	2.5	10.0	2.0
100.0	B	TC212B107◎002□	2.5	8.0	1.5
150.0	B	TC212B157◎002□	3.75	10.0	1.5
220.0	B	TC212B227◎002□	5.5	18.0	1.5
4V, +85°C (2.5V @ +125°C)					
2.2	A	TC212A225◎004□	0.5	6.0	6.0
3.3	P	TC212P335◎004□	0.5	6.0	8.0
3.3	A	TC212A335◎004□	0.5	6.0	6.0
4.7	P	TC212P475◎004□	0.5	6.0	6.0
4.7	A	TC212A475◎004□	0.5	6.0	5.0
6.8	P	TC212P685◎004□	0.5	6.0	7.0
6.8	A	TC212A685◎004□	0.5	6.0	4.0
10.0	P	TC212P106◎004□	0.5	8.0	6.0
10.0	A	TC212A106◎004□	0.5	6.0	3.0
10.0	B	TC212B106◎004□	0.5	6.0	1.5
15.0	A	TC212A156◎004□	0.6	6.0	1.5
15.0	B	TC212B156◎004□	0.6	6.0	1.2
22.0	A	TC212A226◎004□	0.88	6.0	1.5
22.0	B	TC212B226◎004□	0.88	6.0	0.6
33.0	P	TC212P336◎004□	1.32	20.0	2.0

Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.
33.0	A	TC212A336◎004□	1.32	6.0	2.5
33.0	B	TC212B336◎004□	1.32	6.0	0.5
33.0	C	TC212C336◎004Y	1.32	6.0	0.8
47.0	P	TC212P476◎004□	3.80	25.0	4.0
47.0	A	TC212A476◎004□	1.88	6.0	2.0
47.0	B	TC212B476◎004□	1.88	6.0	0.8
47.0	C	TC212C476◎004Y	1.88	6.0	1.0
68.0	B	TC212B686◎004□	2.72	6.0	2.5
68.0	C	TC212C686◎004Y	2.72	6.0	0.5
68.0	D	TC212D686◎004Y	2.72	6.0	0.5
100.0	A	TC212A107◎004□	4.0	18.0	3.0
100.0	B	TC212B107◎004□	4.0	8.0	1.0
100.0	C	TC212C107◎004Y	4.0	8.0	0.35
100.0	D	TC212D107◎004Y	4.0	8.0	0.2
150.0	B	TC212B157◎004□	6.0	15.0	1.0
150.0	C	TC212C157◎004Y	6.0	8.0	0.3
150.0	D	TC212D157◎004Y	6.0	8.0	0.2
220.0	B	TC212B227◎004□	8.8	15.0	0.4
220.0	C	TC212C227◎004Y	8.8	8.0	0.5
220.0	D	TC212D227◎004Y	8.8	8.0	0.3
330.0	B	TC212B337◎004□	13.2	18.0	0.7
330.0	C	TC212C337◎004Y	13.2	8.0	0.8
330.0	D	TC212D337◎004Y	13.2	8.0	0.2
330.0	E	TC212E337◎004Y	13.2	8.0	0.2
470.0	E	TC212E477◎004Y	18.8	8.0	0.2
680.0	E	TC212E687◎004Y	27.2	8.0	0.2
6.3V, +85°C (4.0V @ +125°C)					
1.0	P	TC212P105◎006□	0.5	6.0	15.0
1.0	A	TC212A105◎006□	0.5	6.0	10.0
1.5	P	TC212P155◎006□	0.5	8.0	10.0
1.5	A	TC212A155◎006□	0.5	6.0	6.0
2.2	P	TC212P225◎006□	0.5	8.0	10.0

SPECIFICATIONS

TC212 TYPE

Capacitance (μF)	Case	Part Number	DCL (μA) +25℃ Max.	DF (%) +25℃ 120Hz Max.	ESR(Ω) +25℃ 100kHz Max.	Capacitance (μF)	Case	Part Number	DCL (μA) +25℃ Max.	DF (%) +25℃ 120Hz Max.	ESR(Ω) +25℃ 100kHz Max.
2.2	A	TC212A2250006□	0.5	6.0	6.0	4.7	P	TC212P4750010□	0.5	6.0	8.0
3.3	P	TC212P3350006□	0.5	6.0	5.0	4.7	A	TC212A4750010□	0.5	6.0	3.0
3.3	A	TC212A3350006□	0.5	6.0	6.0	4.7	B	TC212B4750010□	0.5	6.0	1.5
4.7	P	TC212P4750006□	0.5	6.0	6.0	6.8	P	TC212P6850010□	0.68	8.0	3.0
4.7	A	TC212A4750006□	0.5	6.0	4.0	6.8	A	TC212A6850010□	0.68	6.0	3.0
6.8	P	TC212P6850006□	0.5	6.0	8.0	6.8	B	TC212B6850010□	0.68	6.0	1.2
6.8	A	TC212A6850006□	0.5	6.0	3.5	10.0	P	TC212P1060010□	1.0	15.0	6.0
6.8	B	TC212B6850006□	0.5	6.0	3.0	10.0	A	TC212A1060010□	1.0	6.0	1.8
10.0	P	TC212P1060006□	0.63	8.0	6.0	10.0	B	TC212B1060010□	1.0	6.0	0.8
10.0	A	TC212A1060006□	0.63	6.0	2.0	10.0	C	TC212C1060010Y	1.0	6.0	0.6
10.0	B	TC212B1060006□	0.63	6.0	1.0	15.0	A	TC212A1560010□	1.5	6.0	4.0
15.0	P	TC212P1560006□	0.94	10.0	5.0	15.0	B	TC212B1560010□	1.5	6.0	0.7
15.0	A	TC212A1560006□	0.94	6.0	2.0	15.0	C	TC212C1560010Y	1.5	6.0	0.5
15.0	B	TC212B1560006□	0.94	6.0	0.7	22.0	A	TC212A2260010□	2.2	8.0	2.5
22.0	P	TC212P2260006□	1.3	18.0	4.0	22.0	B	TC212B2260010□	2.2	6.0	1.0
22.0	A	TC212A2260006□	1.38	6.0	2.5	22.0	C	TC212C2260010Y	2.2	6.0	0.4
22.0	B	TC212B2260006□	1.38	6.0	0.8	33.0	A	TC212A3360010□	3.3	15.0	4.0
33.0	A	TC212A3360006□	2.07	8.0	1.5	33.0	B	TC212B3360010□	3.3	6.0	1.0
33.0	B	TC212B3360006□	2.07	6.0	0.8	33.0	C	TC212C3360010Y	3.3	6.0	0.4
33.0	C	TC212C3360006Y	2.07	6.0	0.3	33.0	D	TC212D3360010Y	3.3	6.0	0.25
47.0	A	TC212A4760006□	2.96	8.0	2.5	47.0	A	TC212A4760010□	4.7	15.0	1.5
47.0	B	TC212B4760006□	2.96	6.0	0.5	47.0	B	TC212B4760010□	4.7	6.0	0.65
47.0	C	TC212C4760006Y	2.96	6.0	0.3	47.0	C	TC212C4760010Y	4.7	6.0	0.30
68.0	B	TC212B6860006□	4.28	10.0	0.65	47.0	D	TC212D4760010Y	4.7	6.0	0.22
68.0	C	TC212C6860006Y	4.28	6.0	0.2	68.0	B	TC212B6860010□	6.8	10.0	1.5
68.0	D	TC212D6860006Y	4.28	6.0	0.2	68.0	C	TC212C6860010Y	6.8	6.0	0.30
100.0	A	TC212A1070006□	6.3	20.0	2.0	68.0	D	TC212D6860010Y	6.8	6.0	0.20
100.0	B	TC212B1070006□	6.3	10.0	1.5	100.0	B	TC212B1070010□	10.0	15.0	1.0
100.0	C	TC212C1070006Y	6.3	8.0	0.3	100.0	C	TC212C1070010Y	10.0	8.0	0.20
100.0	D	TC212D1070006Y	6.3	8.0	0.2	100.0	D	TC212D1070010Y	10.0	8.0	0.15
150.0	B	TC212B1570006□	9.45	15.0	0.6	150.0	C	TC212C1570010Y	15.0	10.0	0.70
150.0	C	TC212C1570006Y	9.45	8.0	0.3	150.0	D	TC212D1570010Y	15.0	8.0	0.15
150.0	D	TC212D1570006Y	9.45	8.0	0.2	150.0	E	TC212E1570010Y	15.0	8.0	0.15
220.0	B	TC212B2270006□	13.86	18.0	0.7	220.0	D	TC212D2270010Y	22.0	8.0	0.15
220.0	C	TC212C2270006Y	13.86	8.0	0.3	220.0	E	TC212E2270010Y	22.0	8.0	0.15
220.0	D	TC212D2270006Y	13.86	8.0	0.15	330.0	D	TC212D3370010Y	33.0	10.0	0.15
220.0	E	TC212E2270006Y	13.86	8.0	0.15	330.0	E	TC212E3370010Y	33.0	10.0	0.2
330.0	D	TC212D3370006Y	20.79	8.0	0.15	470.0	E	TC212E4770010Y	47.0	10.0	0.2
330.0	E	TC212E3370006Y	20.79	8.0	0.15	16V, +85℃ (10V @ +125℃)					
470.0	D	TC212D4770006Y	29.61	12.0	0.15	0.47	P	TC212P4740016□	0.5	6.0	15.0
470.0	E	TC212E4770006Y	29.61	10.0	0.12	0.68	P	TC212P6840016□	0.5	6.0	15.0
10V, +85℃ (6.3V @ +125℃)						1.0	P	TC212P1050016□	0.5	6.0	10.0
0.68	P	TC212P6840010□	0.5	4.0	15.0	1.0	A	TC212A1050016□	0.5	4.0	8.0
1.0	P	TC212P1050010□	0.5	10.0	10.0	1.5	P	TC212P1550016□	0.5	6.0	10.0
1.0	A	TC212A1050010□	0.5	4.0	8.0	1.5	A	TC212A1550016□	0.5	6.0	8.0
1.5	P	TC212P1550010□	0.5	10.0	6.0	2.2	P	TC212P2250016□	0.5	6.0	15.0
1.5	A	TC212A1550010□	0.5	6.0	6.0	2.2	A	TC212A2250016□	0.5	6.0	6.0
2.2	P	TC212P2250010□	0.5	6.0	8.0	2.2	B	TC212B2250016□	0.5	6.0	3.0
2.2	A	TC212A2250010□	0.5	6.0	6.0	3.3	A	TC212A3350016□	0.52	6.0	5.0
3.3	P	TC212P3350010□	0.5	6.0	10.0	3.3	B	TC212B3350016□	0.52	6.0	2.5
3.3	A	TC212A3350010□	0.5	6.0	4.0	4.7	P	TC212P4750016□	0.8	18.0	10.0

Sunlord

Specifications subject to change without notice. Please check our website for latest information. Revised 2014/04/15

Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110 Tel: 0086-755-29832660 Fax: 0086-755-82269029 E-Mail: sunlord@sunlordinc.com

SPECIFICATIONS

TC212 TYPE

Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.	Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.
4.7	A	TC212A4750016□	0.75	6.0	5.0	10.0	B	TC212B1060020□	2.0	6.0	2.0
4.7	B	TC212B4750016□	0.75	6.0	2.5	10.0	C	TC212C1060020Y	2.0	6.0	1.2
4.7	C	TC212C4750016Y	0.8	6.0	1.5	10.0	D	TC212D1060020Y	2.0	6.0	0.8
6.8	A	TC212A6850016□	1.08	6.0	5.0	15.0	C	TC212C1560020Y	3.0	6.0	1.2
6.8	B	TC212B6850016□	1.08	6.0	2.5	15.0	D	TC212D1560020Y	3.0	6.0	0.8
6.8	C	TC212C6850016Y	1.08	6.0	1.0	22.0	B	TC212B2260020□	4.4	8.0	3.0
10.0	A	TC212A1060016□	1.6	8.0	3.0	22.0	C	TC212C2260020Y	4.4	6.0	0.4
10.0	B	TC212B1060016□	1.6	6.0	0.8	22.0	D	TC212D2260020Y	4.4	6.0	0.5
10.0	C	TC212C1060016Y	1.6	6.0	1.5	33.0	C	TC212C3360020Y	6.6	6.0	0.6
15.0	B	TC212B1560016□	2.4	6.0	2.0	33.0	D	TC212D3360020Y	6.6	6.0	0.4
15.0	C	TC212C1560016Y	2.4	6.0	1.2	47.0	C	TC212C4760020Y	9.4	10.0	0.8
22.0	A	TC212A2260016□	3.52	15.0	2.0	47.0	D	TC212D4760020Y	9.4	6.0	0.6
22.0	B	TC212B2260016□	3.52	8.0	1.5	47.0	E	TC212E4760020Y	9.4	6.0	0.3
22.0	C	TC212C2260016Y	3.52	6.0	1.2	68.0	D	TC212D6860020Y	13.6	6.0	0.4
22.0	D	TC212D2260016Y	3.52	6.0	0.6	68.0	E	TC212E6860020Y	13.6	6.0	0.3
33.0	B	TC212B3360016□	5.28	8.0	1.0	100.0	D	TC212D1070020Y	20.0	8.0	0.2
33.0	C	TC212C3360016Y	5.28	6.0	1.0	100.0	E	TC212E1070020Y	20.0	8.0	0.2
33.0	D	TC212D3360016Y	5.28	6.0	0.5	150.0	E	TC212E1570020Y	30.0	8.0	0.2
47.0	B	TC212B4760016□	7.52	18.0	0.7	25V, +85°C (16V @ +125°C)					
47.0	C	TC212C4760016Y	7.52	6.0	0.8	0.22	A	TC212A2240025□	0.5	4.0	10.0
47.0	D	TC212D4760016Y	7.52	6.0	0.5	0.33	A	TC212A3340025□	0.5	4.0	12.0
68.0	D	TC212D6860016Y	10.8	6.0	0.5	0.47	P	TC212P4740025□	0.5	4.0	8.0
100.0	C	TC212C1070016Y	16.0	10.0	0.7	0.47	A	TC212A4740025□	0.5	4.0	10.0
100.0	D	TC212D1070016Y	16.0	8.0	0.5	0.68	A	TC212A6840025□	0.5	4.0	6.0
150.0	D	TC212D1570016Y	24.0	12.0	0.4	1.0	P	TC212P1050025□	0.5	6.0	8.0
150.0	E	TC212E1570016Y	24.0	8.0	0.15	1.0	A	TC212A1050025□	0.5	4.0	6.0
220.0	D	TC212D2270016Y	35.2	15.0	0.6	1.0	B	TC212B1050025□	0.5	4.0	4.0
220.0	E	TC212E2270016Y	35.2	10.0	0.2	1.5	A	TC212A1550025□	0.5	6.0	5.0
330.0	E	TC212E3370016Y	52.8	10.0	0.2	1.5	B	TC212B1550025□	0.5	6.0	3.5
20V, +85°C (13V @ +125°C)						2.2	A	TC212A2250025□	0.6	6.0	4.0
0.1	P	TC212P1040020□	0.5	4.0	15.0	2.2	B	TC212B2250025□	0.55	6.0	3.0
0.15	P	TC212P1540020□	0.5	4.0	15.0	2.2	C	TC212C2250025Y	0.55	6.0	2.0
0.22	P	TC212P2240020□	0.5	4.0	15.0	3.3	A	TC212A3350025□	0.82	6.0	3.0
0.33	P	TC212P3340020□	0.5	4.0	15.0	3.3	B	TC212B3350025□	0.82	6.0	2.5
0.47	P	TC212P4740020□	0.5	4.0	15.0	3.3	C	TC212C3350025Y	0.82	6.0	2.0
0.68	P	TC212P6840020□	0.5	4.0	15.0	4.7	A	TC212A4750025□	1.17	8.0	3.0
0.68	A	TC212A6840020□	0.5	4.0	10.0	4.7	B	TC212B4750025□	1.17	6.0	1.0
1.0	P	TC212P1050020□	0.5	6.0	15.0	4.7	C	TC212C4750025Y	1.17	6.0	2.4
1.0	A	TC212A1050020□	0.5	4.0	8.0	6.8	B	TC212B6850025□	1.7	6.0	1.2
1.5	A	TC212A1550020□	0.5	6.0	4.5	6.8	C	TC212C6850025Y	1.7	6.0	0.8
1.5	B	TC212B1550020□	0.5	6.0	1.5	6.8	D	TC212D6850025Y	1.7	6.0	0.5
2.2	A	TC212A2250020□	0.5	6.0	4.0	10.0	B	TC212B1060025□	2.5	6.0	2.0
2.2	B	TC212B2250020□	0.5	6.0	3.0	10.0	C	TC212C1060025Y	2.5	6.0	1.4
3.3	A	TC212A3350020□	0.66	6.0	6.0	10.0	D	TC212D1060025Y	2.5	6.0	0.8
3.3	B	TC212B3350020□	0.66	6.0	2.5	15.0	B	TC212B1560025□	3.75	8.0	3.0
4.7	A	TC212A4750020□	0.94	6.0	3.5	15.0	C	TC212C1560025Y	3.75	6.0	1.2
4.7	B	TC212B4750020□	0.94	6.0	2.5	15.0	D	TC212D1560025Y	3.75	6.0	0.8
4.7	C	TC212C4750020Y	0.94	6.0	1.2	22.0	C	TC212C2260025Y	5.5	6.0	1.0
6.8	B	TC212B6850020□	1.36	6.0	2.5	22.0	D	TC212D2260025Y	5.5	6.0	0.6
6.8	C	TC212C6850020Y	1.36	6.0	1.2	33.0	D	TC212D3360025Y	8.25	6.0	0.6
6.8	D	TC212D6850020Y	1.36	6.0	0.8	33.0	E	TC212E3360025Y	8.25	6.0	0.5

Sunlord

Specifications subject to change without notice. Please check our website for latest information. Revised 2014/04/15

Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110 Tel: 0086-755-29832660 Fax: 0086-755-82269029 E-Mail: sunlord@sunlordinc.com

SPECIFICATIONS

TC212 TYPE

Capacitance (μ F)	Case	Part Number	DCL (μ A) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.	Capacitance (μ F)	Case	Part Number	DCL (μ A) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.
47.0	D	TC212D476 $\odot$ 025Y	11.7	6.0	0.4	22.0	D	TC212D226 $\odot$ 035Y	7.7	6.0	0.6
47.0	E	TC212E476 $\odot$ 025Y	11.7	6.0	0.4	22.0	E	TC212E226 $\odot$ 035Y	7.7	6.0	0.3
68.0	E	TC212E686 $\odot$ 025Y	17.0	6.0	0.3	33.0	E	TC212E336 $\odot$ 035Y	11.0	6.0	0.5
100.0	D	TC212D107 $\odot$ 025Y	25.0	10.0	0.7	47.0	E	TC212E476 $\odot$ 035Y	16.5	8.0	0.5
35V, +85°C (20V @ +125°C)						50V, +85°C (32V @ +125°C)					
0.1	P	TC212P104 $\odot$ 035□	0.5	4.0	20.0	0.1	A	TC212A104 $\odot$ 050□	0.5	4.0	15.0
0.1	A	TC212A104 $\odot$ 035□	0.5	4.0	15.0	0.15	A	TC212A154 $\odot$ 050□	0.5	4.0	15.0
0.15	A	TC212A154 $\odot$ 035□	0.5	4.0	12.0	0.15	B	TC212B154 $\odot$ 050□	0.5	4.0	12.0
0.22	A	TC212A224 $\odot$ 035□	0.5	4.0	12.0	0.22	A	TC212A224 $\odot$ 050□	0.5	4.0	15.0
0.33	A	TC212A334 $\odot$ 035□	0.5	4.0	12.0	0.22	B	TC212B224 $\odot$ 050□	0.5	4.0	12.0
0.47	A	TC212A474 $\odot$ 035□	0.5	4.0	10.0	0.33	A	TC212A334 $\odot$ 050□	0.5	4.0	12.0
0.47	B	TC212B474 $\odot$ 035□	0.5	4.0	6.0	0.33	B	TC212B334 $\odot$ 050□	0.5	4.0	2.5
0.68	A	TC212A684 $\odot$ 035□	0.5	4.0	6.0	0.47	A	TC212A474 $\odot$ 050□	0.5	4.0	2.0
0.68	B	TC212B684 $\odot$ 035□	0.5	4.0	6.0	0.47	B	TC212B474 $\odot$ 050□	0.5	4.0	6.0
1.0	A	TC212A105 $\odot$ 035□	0.5	4.0	8.0	0.47	C	TC212C474 $\odot$ 050Y	0.5	4.0	5.0
1.0	B	TC212B105 $\odot$ 035□	0.5	4.0	2.0	0.68	A	TC212A684 $\odot$ 050□	0.5	4.0	3.0
1.5	B	TC212B155 $\odot$ 035□	0.52	6.0	4.0	0.68	B	TC212B684 $\odot$ 050□	0.5	4.0	5.0
1.5	C	TC212C155 $\odot$ 035Y	0.52	6.0	3.0	0.68	C	TC212C684 $\odot$ 050Y	0.5	4.0	4.0
2.2	A	TC212A225 $\odot$ 035□	0.77	6.0	3.0	1.0	B	TC212B105 $\odot$ 050□	0.5	6.0	4.0
2.2	B	TC212B225 $\odot$ 035□	0.77	6.0	3.0	1.0	C	TC212C105 $\odot$ 050Y	0.5	4.0	3.5
2.2	C	TC212C225 $\odot$ 035Y	0.77	6.0	2.5	1.5	B	TC212B155 $\odot$ 050□	0.75	6.0	3.5
3.3	B	TC212B335 $\odot$ 035□	1.15	6.0	3.0	1.5	C	TC212C155 $\odot$ 050Y	0.75	6.0	2.5
3.3	C	TC212C335 $\odot$ 035Y	1.15	6.0	2.0	2.2	B	TC212B225 $\odot$ 050□	1.1	6.0	1.5
4.7	B	TC212B475 $\odot$ 035□	1.64	6.0	1.0	2.2	C	TC212C225 $\odot$ 050Y	1.1	6.0	3.0
4.7	C	TC212C475 $\odot$ 035Y	1.64	6.0	2.0	2.2	D	TC212D225 $\odot$ 050Y	1.1	6.0	2.0
4.7	D	TC212D475 $\odot$ 035Y	1.64	6.0	1.0	3.3	B	TC212B335 $\odot$ 050□	1.65	6.0	1.2
6.8	C	TC212C685 $\odot$ 035Y	2.38	6.0	1.2	3.3	C	TC212C335 $\odot$ 050Y	1.65	6.0	2.0
6.8	D	TC212D685 $\odot$ 035Y	2.38	6.0	0.8	3.3	D	TC212D335 $\odot$ 050Y	1.65	6.0	1.0
10.0	C	TC212C106 $\odot$ 035Y	3.5	6.0	1.5	4.7	D	TC212D475 $\odot$ 050Y	2.35	6.0	0.8
10.0	D	TC212D106 $\odot$ 035Y	3.5	6.0	0.6	6.8	D	TC212D685 $\odot$ 050Y	3.4	6.0	0.7
10.0	E	TC212E106 $\odot$ 035Y	3.5	6.0	0.6	10.0	D	TC212D106 $\odot$ 050Y	5.0	6.0	0.7
15.0	D	TC212D156 $\odot$ 035Y	5.25	6.0	0.8	10.0	E	TC212E106 $\odot$ 050Y	5.0	6.0	0.4
15.0	E	TC212E156 $\odot$ 035Y	5.25	6.0	0.6	15.0	E	TC212E156 $\odot$ 050Y	7.5	6.0	0.4

ATC214 TYPE

Capacitance (μ F)	Case	Part Number	DCL (μ A) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.	Capacitance (μ F)	Case	Part Number	DCL (μ A) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.
4V, +85°C (2.5V @ +125°C)						6.3V, +85°C (4.0V @ +125°C)					
2.2	A	ATC214A225 $\odot$ 004□	0.5	6.0	6.0	1.5	A	ATC214A155 $\odot$ 006□	0.5	6.0	6.0
3.3	A	ATC214A335 $\odot$ 004□	0.5	6.0	6.0	2.2	A	ATC214A225 $\odot$ 006□	0.5	6.0	6.0
4.7	B	ATC214B475 $\odot$ 004□	0.5	6.0	6.0	3.3	B	ATC214B335 $\odot$ 006□	0.5	6.0	8.0
6.8	B	ATC214B685 $\odot$ 004□	0.5	6.0	6.0	4.7	B	ATC214B475 $\odot$ 006□	0.5	6.0	10.0
10.0	B	ATC214B106 $\odot$ 004□	0.5	6.0	1.5	6.8	B	ATC214B685 $\odot$ 006□	0.5	6.0	1.2
15.0	C	ATC214C156 $\odot$ 004Y	0.5	6.0	1.5	10.0	C	ATC214C106 $\odot$ 006Y	0.6	6.0	0.6
22.0	C	ATC214C226 $\odot$ 004Y	0.6	6.0	1.0	15.0	C	ATC214C156 $\odot$ 006Y	0.9	6.0	0.6
33.0	D	ATC214D336 $\odot$ 004Y	1.3	6.0	1.0	22.0	D	ATC214D226 $\odot$ 006Y	1.3	6.0	0.5
47.0	D	ATC214D476 $\odot$ 004Y	1.9	6.0	1.0	33.0	D	ATC214D336 $\odot$ 006Y	2.1	6.0	0.3
68.0	D	ATC214D686 $\odot$ 004Y	2.7	6.0	0.5	47.0	D	ATC214D476 $\odot$ 006Y	3.0	6.0	0.3
100	D	ATC214D107 $\odot$ 004Y	4.0	8.0	0.3	68.0	D	ATC214D686 $\odot$ 006Y	4.3	6.0	0.2

Sunlord

Specifications subject to change without notice. Please check our website for latest information. Revised 2014/04/15

Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110 Tel: 0086-755-29832660 Fax: 0086-755-82269029 E-Mail: sunlord@sunlordinc.com

SPECIFICATIONS

ATC214 TYPE

Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.	Capacitance (μF)	Case	Part Number	DCL (μA) +25°C Max.	DF (%) +25°C 120Hz Max.	ESR(Ω) +25°C 100kHz Max.
10V, +85°C (6.3V @ +125°C)						0.47	A	ATC214A474◎025□	0.5	4.0	10.0
1.0	A	ATC214A105◎010□	0.5	4.0	6.0	0.68	B	ATC214B684◎025□	0.5	4.0	6.0
1.5	A	ATC214A155◎010□	0.5	6.0	6.0	1.0	B	ATC214B105◎025□	0.5	4.0	4.0
2.2	B	ATC214B225◎010□	0.5	6.0	3.0	1.5	B	ATC214B155◎025□	0.5	6.0	3.5
3.3	B	ATC214B335◎010□	0.5	6.0	3.0	2.2	C	ATC214C225◎025Y	0.6	6.0	2.0
4.7	B	ATC214B475◎010□	0.5	6.0	1.5	3.3	C	ATC214C335◎025Y	0.8	6.0	2.0
6.8	C	ATC214C685◎010Y	0.7	6.0	0.8	4.7	D	ATC214D475◎025Y	1.2	6.0	1.5
10.0	C	ATC214C106◎010Y	1.0	6.0	0.6	6.8	D	ATC214D685◎025Y	1.7	6.0	1.0
15.0	C	ATC214C156◎010Y	1.5	6.0	0.5	10.0	D	ATC214D106◎025Y	2.5	6.0	0.8
22.0	D	ATC214D226◎010Y	2.2	6.0	0.4	15.0	D	ATC214D156◎025Y	3.8	6.0	0.8
33.0	D	ATC214D336◎010Y	3.3	6.0	0.25	35V, +85°C (20V @ +125°C)					
47.0	D	ATC214D476◎010Y	4.7	6.0	0.22	0.1	A	ATC214A104◎035□	0.5	4.0	15.0
16V, +85°C (10V @ +125°C)						0.15	A	ATC214A154◎035□	0.5	4.0	12.0
0.68	A	ATC214A684◎016□	0.5	6.0	10.0	0.22	A	ATC214A224◎035□	0.5	4.0	12.0
1.0	A	ATC214A105◎016□	0.5	4.0	6.0	0.33	A	ATC214A334◎035□	0.5	4.0	12.0
1.5	B	ATC214B155◎016□	0.5	6.0	4.0	0.47	B	ATC214B474◎035□	0.5	4.0	2.5
2.2	B	ATC214B225◎016□	0.5	6.0	3.0	0.68	B	ATC214B684◎035□	0.5	4.0	2.5
3.3	B	ATC214B335◎016□	0.5	6.0	2.5	1.0	B	ATC214B105◎035□	0.5	4.0	2.0
4.7	C	ATC214C475◎016Y	0.8	6.0	1.5	1.5	B	ATC214B155◎035□	0.5	4.0	2.0
6.8	C	ATC214C685◎016Y	1.1	6.0	1.0	1.5	C	ATC214C155◎035Y	0.5	6.0	2.5
10.0	C	ATC214C106◎016Y	1.6	6.0	1.5	2.2	C	ATC214C225◎035Y	0.8	6.0	1.5
15.0	D	ATC214D156◎016Y	2.4	6.0	0.5	3.3	D	ATC214D335◎035Y	1.2	6.0	1.5
22.0	D	ATC214D226◎016Y	3.5	6.0	0.25	4.7	D	ATC214D475◎035Y	1.6	6.0	1.0
33.0	D	ATC214D336◎016Y	5.3	6.0	0.25	6.8	D	ATC214D685◎035Y	2.4	6.0	0.8
20V, +85°C (13V @ +125°C)						10.0	D	ATC214D106◎035Y	3.5	6.0	0.6
0.47	A	ATC214A474◎020□	0.5	4.0	10.0	50V, +85°C (32V @ +125°C)					
0.68	A	ATC214A684◎020□	0.5	4.0	8.0	0.1	A	ATC214A104◎050□	0.5	4.0	15.0
1.0	B	ATC214B105◎020□	0.5	4.0	6.0	0.15	B	ATC214B154◎050□	0.5	4.0	12.0
1.5	B	ATC214B155◎020□	0.5	6.0	1.5	0.22	B	ATC214B224◎050□	0.5	4.0	12.0
2.2	B	ATC214B225◎020□	0.5	6.0	3.0	0.33	B	ATC214B334◎050□	0.5	4.0	2.5
3.3	C	ATC214C335◎020Y	0.7	6.0	1.5	0.47	C	ATC214C474◎050Y	0.5	4.0	5.0
4.7	C	ATC214C475◎020Y	0.9	6.0	1.2	0.68	C	ATC214C684◎050Y	0.5	4.0	4.0
6.8	D	ATC214D685◎020Y	1.4	6.0	0.8	1.0	C	ATC214C105◎050Y	0.5	4.0	3.5
10.0	D	ATC214D106◎020Y	2.0	6.0	0.8	1.5	D	ATC214D155◎050Y	0.8	6.0	2.5
15.0	D	ATC214D156◎020Y	3.0	6.0	0.8	2.2	D	ATC214D225◎050Y	1.1	6.0	2.0
22.0	D	ATC214D226◎020Y	4.4	6.0	0.5	3.3	D	ATC214D335◎050Y	1.7	6.0	1.0
25V, +85°C (16V @ +125°C)						4.7	D	ATC214D475◎050Y	2.4	6.0	0.8
0.33	A	ATC214A334◎025□	0.5	4.0	12.0						

※◎:Capacitance tolerance code (K=±10%, M=±20%);

※□: Internal code (A=Black molded case, Ink marking; B=Black molded case, Laser marking; Y=Yellow molded case, Laser marking).